



RH18/450ER
RH22/620ER



Lightweight two-mode professional rotary hammers most efficient for drilling holes in concrete, stones and bricks. Ideally suitable for series of light anchoring operations.

SPECIAL FEATURES

- 2-modes: drilling and hammer drilling
- Left-right rotation trough rotating brush holder provides same speed levels on both sides
- Increased impact rate of maximum 7500 min⁻¹ ensures faster drilling operations in most commonly used diameters 6, 8, 10 mm (RH18/450ER)
- Safety clutch protects operator from injuries
- Electronic speed regulation ensures drilling precision
- Compact size and small weight ensure work convenience even in confined spaces
- 4 meter power cable with rubber insulation enables the user to move freely
- Ergonomic design with rubberized handle.

TECHNICAL DATA		RH18/450ER	RH22/620ER
Rated power	W	450	620
Rated voltage / frequency	V~Hz	230 ~ 50	230 ~ 50
No-load speed	min ⁻¹	0-1650	0-1100
No-load hammer rate	min ⁻¹	0-7500	0-5060
Impact energy	J	1,2	2,2
Working modes		2	2
Drilling diameter in concrete	mm	18	22
Drilling diameter in steel	mm	13	13
Drilling diameter in wood	mm	24	30
Weight according EPTA-Procedure 01/2003	kg	2.00	2.50
Item No.		138170379	138170479
Standart equipment	Additional handle, Keyed Chuck, SDS Plus adapter, bit holder (RH18/450ER), plastic case.		

ROTARY HAMMERS,
DEMOLITION HAMMERS

Rotary Hammers SDS-plus	26
Rotary Hammers SDS-Max	31
Demolition Hammers SDS-Max	32
Drill bits and Chisels	34